




STEP-BY-STEP DIRECTIONS -

BELTED MIDI DRESS



Fabric - Printed Polyester, Chiffon or Similar

Seam margin - Shoulders & Side seam Attach is 1.2 CM (Included the pattern)


Belt Seam margin is 1.2 CM (Included the pattern)

There is no seam margin for binding area (Armhole)


Fabric Requirnments - Average 62 inches / 1.6 meters (60" Cutt-able Fabric Width)
See below for fabric way..

BLOCK FOR FUSING

Apply the woven fusing to the front and back neck facing the wrong side of the fabric




Follow cutting instructions as given below - Follow the grain line




STEP 01. Front DART closing- Follow dart line - Stitch on dart marking -Start at notch mark & finish at the end of marking - See below picture - Use normal lockstitch machine



STEP 02. Overlock the out side of the front & back facing panels - See below images



STEP 03. Attach the front and back neck facing to the front and back body panels
Lay your back & front dress pieces with face side upwards & lay the facing pieces on top with right sides facing downwards. Then attach the line marked as below picture - follow 1cm seam margin.



STEP 04. Turn back & front neck facings, then do 1/6" edge stitch along the neck area if you prefer. If not leave it as a plain edge (need to be pressed prefect before adding the edge stitch

STEP 05. Lay your back & front dress pieces with face side downwards. Attach shoulders with 1.2cm seam margin - Use 5 thread overlock or Serger machine.

STEP 06. Apply the Binding to Armhole - You can use 8mm bias binding FOLDER or a manual binging process - You can get some idea of binding process by seeing this video link

<https://www.youtube.com/watch?v=kNPzQMuOyCQ>

STEP 07. Make belt loops - size as per your choice - follow these directions

- Fold your strip (1 1/4" width) in half lengthwise and press.
- Fold the long raw edges into the centerfold and press.
- Fold by 1/4" again lengthwise, and press the original centerfold again. (3/8" finish)
- Stitch close to the edge of both long sides of the strip.
- Cut into 2 loops, each 3 1/2" long.

STEP 08. Lay your back & front dress pieces with face side downwards. Joint Side Seam - Follow 1.2 cm seam margin - Use 5 thread overlock machine or Serger. Please make sure to mark for loops with chalk (Follow waist notch mark for Belt loops)


STEP 09. Stitch bottom hem. Overlock all around of bottom hem. Then turn it 1cm backward. Next, do the 0.8mm topstitch or you can use 0.8 mm hem folder.

STEP 10. Belt making..

- Fold your BELT in half lengthwise and press (Follow dash line) Fold your belt piece with face side inner



- Insert thick thread to between panel (for easy turn it over) & 1cm Stitch around the belt Follow the image.



- Then turn it over by stretching from the thread & clean finish the other end.

OR

You can make this belt also same like this - see below video link

<https://youtu.be/0GRK-pdqUNM>

Congratulations - You have made
Belted V Neck Midi Dress
Copyrighted - ZerDesigner - 2022

Thank you for your purchase! If you are happy with this , please take a minute to review it ★★★★★